

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









VCO-104/104TC

rfmd >>> VCO-104/104TC

Nominal Operating Parameters

| Parameter | Specification | | | 11-24 | |
|--------------------------------------|---------------|------|-------|---------|------------------------|
| | Min | Тур | Max | Unit | Condition |
| General Performance | | | | | |
| Frequency Range | 100 | | 200 | MHz | 100% Production Tested |
| Tuning Voltage : | | | | | |
| 100MHz | 0 | 1.4 | | Vdc | 100% Production Tested |
| 200MHz | | 16.8 | 20 | Vdc | 100% Production Tested |
| Tuning Sensitivity: | | | | | |
| 100MHz | 4.8 | 6.4 | 8 | MHz/V | 100% Production Tested |
| 125MHz | 5.3 | 7.1 | 8.9 | MHz/V | 100% Production Tested |
| 150MHz | 5.6 | 7.5 | 9.4 | MHz/V | 100% Production Tested |
| 175MHz | 5.7 | 7.6 | 9.5 | MHz/V | 100% Production Tested |
| 200MHz | 2.4 | 3.2 | 4.4 | MHz/V | 100% Production Tested |
| Output Power | 10 | 12.5 | 16 | dBm | 100% Production Tested |
| Output Phase Noise: | | | | | |
| 10kHz | | -99 | -93 | dBc/Hz | 100% Production Tested |
| 100kHz | | -122 | -116 | dBc/Hz | 100% Production Tested |
| 1000kHz | | -144 | -138 | dBc/Hz | 100% Production Tested |
| Power Supply | 14.75 | 15 | 15.25 | V | 100% Production Tested |
| Supply Current | | 12.5 | 15 | mA | 100% Production Tested |
| Harmonic Suppression: | | | | | |
| 2nd Harmonic | | -12 | -10 | dBc | 100% Production Tested |
| 3rd Harmonic | | -12 | -10 | dBc | 100% Production Tested |
| Spurious (Non-Harmonic) | | | -80 | dBc | |
| Frequency Pushing – 14.75V to 15.25V | | 0.3 | 1 | MHz p-p | |
| Frequency Pulling – 12 dBRL | | 3 | 6 | MHz p-p | |
| Output Impedance | | 50 | | Ω | |
| Modulation: | | | | | |
| Bandwidth | 250 | 350 | | kHz | |
| Input Impedance | | 0.05 | | kΩ | |

Package: TO-8 (Cir), $0.504 \times 0.504 \times 0.27$ inches

VCO-104 Temperature Range: 0°C to 70°C

VCO-104TC Temperature Range: -55°C to 100°C

DS140311