



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# VCO-114/114TC

## Nominal Operating Parameters



Parameter	Specification			Unit	Condition
	Min	Typ	Max		
<b>General Performance</b>					
Frequency Range	60		120	MHz	100% Production Tested
Tuning Voltage :					
60MHz	0	1.2		Vdc	100% Production Tested
120MHz		17	20	Vdc	
Tuning Sensitivity:					
60MHz	2.3	3	3.8	MHz/V	100% Production Tested
75MHz	3.1	4.2	5.2	MHz/V	
90MHz	3.8	5	6.3	MHz/V	
105MHz	3	4	5.1	MHz/V	
120MHz	1.6	2.2	2.7	MHz/V	
Output Power	10	12.5	16	dBm	
Output Phase Noise:					
10kHz		-110	-104	dBc/Hz	100% Production Tested
100kHz		-130	-124	dBc/Hz	
1000kHz		-150	-144	dBc/Hz	
Power Supply	14.75	15	15.25	V	
Supply Current		12.5	15	mA	
Harmonic Suppression:					
2nd Harmonic		-15	-10	dBc	100% Production Tested
3rd Harmonic		-12	-10	dBc	
Spurious (Non-Harmonic)			-80	dBc	
Frequency Pushing – 14.75V to 15.25V		0.05	0.2	MHz p-p	
Frequency Pulling – 12dBRL		1	3	MHz p-p	
Output Impedance		50		$\Omega$	
Modulation:					
Bandwidth	100	175		kHz	
Input Impedance		0.05		k $\Omega$	

**Package:** TO-8 (Cir), 0.504 x 0.504 x 0.27 inches

**VCO-114 Temperature Range:** 0°C to 70°C

**VCO-114TC Temperature Range:** -55°C to 100°C

RF Micro Devices Inc. 7628 Thorndike Road, Greensboro, NC 27409-9421  
 For sales or technical support, contact RFMD at +1.336.678.5570 or [customerservice@rfmd.com](mailto:customerservice@rfmd.com).

DS140312

RF MICRO DEVICES® and RFMD® are trademarks of RFMD, LLC. BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed for use by RFMD. All other trade names, trademarks, and registered trademarks are the property of their respective owners. ©2013, RF Micro Devices, Inc.