



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



VCO-118/118TC

rfmd 
VCO-118/118TC



Nominal Operating Parameters

Parameter	Specification			Unit	Condition
	Min	Typ	Max		
General Performance					
Frequency Range	250		500	MHz	100% Production Tested
Tuning Voltage :					
250MHz	0	1.3		Vdc	100% Production Tested
500MHz		17.6	20	Vdc	
Tuning Sensitivity:					
250MHz	11.9	15.8	19.8	MHz/V	100% Production Tested
312.5MHz	12.6	16.8	21	MHz/V	
375MHz	14.9	19.8	24.8	MHz/V	
437.5MHz	13.1	17.4	21.8	MHz/V	
500MHz	6.2	8.3	10.8	MHz/V	
Output Power	10	13	16	dBm	
Output Phase Noise:					
10kHz		-100	-94	dBc/Hz	100% Production Tested
100kHz		-123	-117	dBc/Hz	
1000kHz		-148	-142	dBc/Hz	
Power Supply	14.75	15	15.25	V	
Supply Current		14.5	16	mA	
Harmonic Suppression:					
2nd Harmonic		-12	-10	dBc	100% Production Tested
3rd Harmonic		-12	-10	dBc	
Spurious (Non-Harmonic)			-80	dBc	
Frequency Pushing – 14.75V to 15.25V		1	3	MHz p-p	
Frequency Pulling – 12dBRL		10	13	MHz p-p	
Output Impedance		50		Ω	
Modulation:					
Bandwidth	5000	10000		kHz	
Input Impedance		0.05		k Ω	

Package: TO-8 (Cir), 0.504 x 0.504 x 0.27 inches

VCO-118 Temperature Range: 0°C to 70°C

VCO-118TC Temperature Range: -55°C to 100°C

RF Micro Devices Inc. 7628 Thorndike Road, Greensboro, NC 27409-9421
For sales or technical support, contact RFMD at +1.336.678.5570 or customerservice@rfmd.com.

DS140313

RF MICRO DEVICES® and RFMD® are trademarks of RFMD, LLC. BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed for use by RFMD. All other trade names, trademarks, and registered trademarks are the property of their respective owners. ©2013, RF Micro Devices, Inc.