



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



VCO-204/204TC

Nominal Operating Parameters

rfmd **VCO-204/204TC**



Parameter	Specification			Unit	Condition
	Min	Typ	Max		
General Performance					
Frequency Range	100		200	MHz	100% Production Tested
Tuning Voltage :					
100MHz	0	1.3		Vdc	100% Production Tested
200MHz		17.9	20	Vdc	
Tuning Sensitivity:					
100MHz	4.8	6.4	8	MHz/V	100% Production Tested
125MHz	4.7	6.3	7.8	MHz/V	
150MHz	5.8	7.7	9.7	MHz/V	
175MHz	4.7	6.3	7.8	MHz/V	
200MHz	2.6	3.5	4.4	MHz/V	
Output Power	10	13	16	dBm	
Output Phase Noise:					
10kHz		-112	-106	dBc/Hz	100% Production Tested
100kHz		-135	-129	dBc/Hz	
1000kHz		-155	-149	dBc/Hz	
Power Supply	14.75	15	15.25	V	
Supply Current		13.5	15	mA	
Harmonic Suppression:					
2nd Harmonic		-25	-20	dBc	100% Production Tested
3rd Harmonic		-18	-15	dBc	
Spurious (Non-Harmonic)			-80	dBc	
Frequency Pushing – 14V to 16V		0.5	0.8	MHz p-p	
Frequency Pulling – 12dBRL		3	4	MHz p-p	
Output Impedance		50		Ω	
Modulation:					
Bandwidth	4000	7000		kHz	
Input Impedance		0.05		k Ω	

Package: TO-8 (Cir), 0.504 x 0.504 x 0.27 inches

VCO-204 Temperature Range: 0°C to 70°C

VCO-204TC Temperature Range: -55°C to 100°C

RF Micro Devices Inc. 7628 Thorndike Road, Greensboro, NC 27409-9421
 For sales or technical support, contact RFMD at +1.336.678.5570 or customerservice@rfmd.com.

DS140313

RF MICRO DEVICES® and RFMD® are trademarks of RFMD, LLC. BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed for use by RFMD. All other trade names, trademarks, and registered trademarks are the property of their respective owners. ©2013, RF Micro Devices, Inc.