

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








DESCRIPTION	DATE	APPROVED				
Mounting Hole Update	04/09/09	T. Y.				
Removed -102 and -134 Parts	08/25/09	T. Y.				
Tolerance Update on .475" Thickness	09/09/10	T. Y.				
Updated Notes with Mounting Instructions	02/05/14	J. C.				
Material Update	10/22/15	J. C.				
	Mounting Hole Update Removed -102 and -134 Parts Tolerance Update on .475" Thickness Updated Notes with Mounting Instructions	Mounting Hole Update 04/09/09 Removed -102 and -134 Parts 08/25/09 Tolerance Update on .475" Thickness 09/09/10 Updated Notes with Mounting Instructions 02/05/14				





PART NO.	A ±.015 (.38)	B ±.015 (.38)	SW 1/16" PCB
VG2-2	2.0 (50.8)	1.5 (38.1)	
VG2-25	2.5 (63.5)	1.5 (38.1)	
VG2-3	3.0 (76.2)		
VG2-35	3.5 (88.9)		
VG2-4	4.0 (101.6)		
VG2-45	4.5 (114.3)	2.0 (50.8)	.076 (1.9)
VG2-5	5.0 (127.0)	, ,	, ,
VG2-55	5.5 (139.7)		
VG2-6	6.0 (152.4)		

- 3. MOUNTING INSTRUCTIONS: INSERT MOUNTING PEG INTO .146" HOLE AND TAPPING SCREW THROUGH SECOND .146" HOLE. PITCH IS .281".
- 2. MATERIAL: NYLON 66, 15% GLASS, 94V-0, BLACK.
- 1. GENERAL SPECIFICATIONS: BIVAR MOLDED COMPONENT SPECIFICATION BV00-E101.

