



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





VP-600SB Non-Contact VoltProbe®

Designed for safety and limited troubleshooting without the expense. Fits conveniently in a shirt pocket, tool belt, or pouch.

- 3 way voltage alert:
 - It beeps
 - It lights
 - It vibrates
- Non-contact method of voltage testing
- Test for AC voltage cables, circuit breakers, wall sockets, junction boxes, fuses and breaks in wires
- Totally insulated, no exposed metal or conductive parts
- CAT III 600V

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



VP-600SB Non-Contact VoltProbe

Data Sheet

Specifications

General Specifications	
Operating voltage	100-600 VAC
Operating Temperature	5°C to +40°C (41°F to 104 °F); < 90% RH
Environment	< 2000m, indoor operation
Power	(2) AAA batteries 1.5 volts alkaline.
Dimensions	132 x 28 x 23mm (5.2 x 1.1 x 0.9")
Weight	49 gr(1.7 oz)
C E EMC	EN 61326-1:2006
Sensitivity	Illuminates red, vibrates and beeps at 4mm (0.16") distance from a wire carrying 120 VAC.



Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
Amprobe Test Tools Europe
Beha-Amprobe GmbH
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved.
03/2009 3465327 Rev A