



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



9-10 POSITION
MINI-CON-X[®]
SEALED CONNECTORS



Switchcraft[®]
CONXALL[®]


HARSH ENVIRONMENT CONNECTIVITY SOLUTIONS



KEY FEATURES

- Available with 9 or 10 #22 contacts
- Cable End, Panel Mount, Cable to Cable, and other options from the Mini-Con-X® series available
- Rated for 3 Amps, 150 VAC
- Made from f1 rated, UV resistant thermoplastic
- See Switchcraft.com for full specifications and full Mini-Con-X series part number list
- Made by Switchcraft/ Conxall in the USA

RECOMMENDED PANEL CUTOUT




PART NUMBERS


W	X	8	XX	-	XXX	-	XXX	X
Connector Type:				Special Features				
6: Cable End				W: Winged Coupling Ring				
7: Panel Mount				Cable-end and Cable-to-cable				
8: Cable to Cable				Backshell with Grommet -				
Contacts Style:				Cable O.D. Range:				
80: Crimp				513: 0.13-0.15" (3.3 -3.8 mm)				
81: PC Tail Standard				516: 0.16-0.18" (4.1 -4.6 mm)				
82: Solder				519: 0.19-0.21" (4.8 -5.3 mm)				
Positions & Contact Types:				522: 0.22-0.25" (5.6 -6.3 mm)				
9PG: 9 Male Pins				528: 0.26-0.285" (6.6 -7.2 mm)				
9SG: 9 Female Sockets				Panel Mount:				
10PG: 10 Male Pins				300: with Hex Nut & Gasket				
10SG: 10 Female Sockets				3ES: 300 with Epoxy				

CONFIGURATIONS

(Panel Mount Wire View)



9-Position
Pin or Socket Contacts



10-Position
Pin or Socket Contacts