



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Clock Generator

Part No.	W83116WG-511
Datasheet	 Request
Description	<p>The W83116WG-511 is a low power clock synthesizer for Intel® Broadwater series chipsets, which has low power differential outputs, an integrated Voltage regulator, as well as an integrated 33Ω series resistor. It also provides all of the clocks required for the high-speed microprocessor, and step-less frequency programming.</p> <p>The W83116WG-511 supports 32 different frequencies of CPU, PCI, PCIEX clock setting, as well as SATA and DOT clock outputs. All clocks are externally selectable with smooth transitions.</p> <p>Programming the registers through I²C serial bus interface can enable or disable each clock output, reduce EMI by -0.5% down type spread spectrum or programmable S.S.T. scale. Dynamic over-clocking is also available.</p> <p>The W83116WG-511 accepts a 14.318 MHz reference crystal as its input and runs on a 3.3V power supply.</p>
Features	<ul style="list-style-type: none"> › 3 Differential pairs of CPU clock outputs › 4x 3V66 clock outputs, and 10x PCI synchronous clocks › 24_48Mhz clock output for super I/O, and 48 MHz clock output for USB. › Skew form CPU to PCI clock 1 to 4 ns, center 2.6 ns › Smooth frequency switch with selections from 66.8 to 200MHz › Step-less frequency programming › I²C 2-Wire serial interface and support byte read/write and block read/write. › -0.5% and +/- 0.25% center type spread spectrum or programmable S.S.T. scale to reduce EMI › Programmable registers to enable/stop each output and select modes › Watch Dog Timer and RESET# output pins
Diagram	N/A
Package	W83116WG-511: TSSOP 64 Pb-free package
Other Files	N/A
Development Tools	N/A
Others	N/A

Contact us: ComputerIC@nuvoton.com