



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Features:**

- **High speed, low latency wireless serial data transmission**
- **Robust 2.4 GHz frequency hopping spread spectrum technology**
- **3.3 volt operation, low power consumption**
- **Small size, light weight**
- **Certified for unlicensed operation in the USA, Canada and Europe**


**Benefits:**

- **Suitable for point-to-point and point-to-multipoint networks**
- **High immunity to interference and multipath fading**
- **Ideal for battery powered devices**
- **Easy to integrate**
- **Worldwide license-free operation**
- **RoHS Compliant**

WIT2410 transceiver modules are designed to transmit serial data using highly robust 2.4 GHz frequency hopping spread spectrum (FHSS) technology. WIT2410 modules employ Murata's beacon-synchronized TDMA at an RF data rate of 460.8 kb/s to achieve very low transmission latency. WIT2410 transceivers are suitable for both point-to-point and point-to-multipoint networks. FHSS technology provides strong immunity to both interference and multipath fading. The small size, light weight and low power consumption of these transceiver modules make them suitable for a wide variety of applications. WIT2410 modules are certified for unlicensed operation in the USA, Canada and Europe.

**WIT2410M4G  
WIT2410S4G**

**FHSS  
Transceiver  
Modules**



Shown with shield removed

**General Specifications**

RF Frequency Range	2400 to 2483 MHz																								
Radio Certifications	FCC Part 15.247, Canadian RSS-210 and European ETS 300.328																								
Operating Range	Indoor - 450 to 900 ft, outdoor - 3000 ft with dipole antenna, more than 6 miles with gain antennas																								
Network Topologies	Point-to-point and point-to-multipoint (star)																								
Network Protocol	Dynamically assigned TDMA with support for up to 62 remotes																								
Error Detection and Correction	24-bit CRC and ARQ																								
Serial Data Interface	Asynchronous (UART) CMOS signals, 3.3 V, 5 V tolerant																								
Serial Data Rate	Up to 230.4 kb/s, software selectable																								
RF Data Rate	460.8 kb/s																								
Number of Frequency Channels	75																								
RF Bandwidth	750 kHz																								
Transmit Power Output	10 or 18 dBm, software selectable																								
Receiver Sensitivity	-93 dBm for 10-5 BER																								
Supply voltage	3.3 to 10 V																								
Current Consumption 18 dBm Transmit Power, 115.2 kb/s Serial Data Rate	<table border="0"> <tr> <td>Remote</td> <td>Sleep</td> <td>50 <math>\mu</math>A</td> <td>Base Station</td> <td>Continuous</td> <td>90 mA</td> </tr> <tr> <td>Operation:</td> <td>Standby</td> <td>22 mA</td> <td>Operation:</td> <td>Peak (TX)</td> <td>100 mA</td> </tr> <tr> <td></td> <td>Typical</td> <td>40 mA</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Peak (TX)</td> <td>90 mA</td> <td></td> <td></td> <td></td> </tr> </table>	Remote	Sleep	50 $\mu$ A	Base Station	Continuous	90 mA	Operation:	Standby	22 mA	Operation:	Peak (TX)	100 mA		Typical	40 mA					Peak (TX)	90 mA			
Remote	Sleep	50 $\mu$ A	Base Station	Continuous	90 mA																				
Operation:	Standby	22 mA	Operation:	Peak (TX)	100 mA																				
	Typical	40 mA																							
	Peak (TX)	90 mA																							
Size	80.2 x 46.5 x 8.6 mm																								
Weight	35 g																								
WIT2410M4G I/O Pin Direction	I/O connector pins point down (PCB interface)																								
WIT2410S4G I/O Pin Direction	I/O connector pins point up (cable connector interface)																								
Operating Temperature	-40 C to +70 C																								
Humidity	20% to 90% (non-condensing)																								



### Fast

WIT2410 modules transmit at an RF data rate of 460.8 kb/s using beacon-synchronized TDMA to achieve very low transmission latency in point-to-point cable replacement applications or point-to-multipoint (star) network applications. Serial communications between a WIT2410 module and its host can run at up to 230.4 kb/s to further speed data communication.

### Reliable

WIT2410 modules provide both reliable communication and reliable operation. Using highly robust frequency hopping spread spectrum technology, WIT2410 modules provide strong immunity to interference and multipath fading. Using a 24-bit CRC for error detection, automatic retransmit request (ARQ) and a 3K data buffer, error-free transparent communication is automatic. Built-in data scrambling adds a measure of security. Reliable operation is assured through Murata's stringent QA processes. All WIT2410 modules are manufactured in an ISO9000 certified facility.

### Simple

Simple to integrate and use, the WIT2410's default parameter settings work for most applications. For other applications, software control makes changing parameter settings easy. The WIT2410, with its small size and low power consumption, is simple to integrate into your product. The WIT2410's RS-232 style interface with standard 3.3 volt CMOS signal levels makes integration easy. Since WIT2410 modules are certified for license free operation in the USA, Canada and Europe, your WIT2410 based product does not have to repeat radio regulatory approval.

### Versatile

WIT2410 operating parameters are configurable under software control. Even the transmitter power level can be selected using a straight-forward command set. Both point-to-point and point-to-multipoint modes are supported. Baud rates from 1.2 to 230.4 kb/s are provided for serial communication between a WIT2410 and its host. A number of non-standard baud rates are supported as well. Measuring just 80.2 x 46.5 x 8.6 mm and weighing 35 grams, the WIT2410 can be integrated into fixed, portable or handheld devices with little impact on the size and weight. The low 3.3 volt operating voltage and 22 mA standby current makes the WIT2410 well suited to battery operation.

### Connector I/O Pins

Pin	Signal	Type	Description
1	GND	-	Signal and chassis ground
2	TxD	Input	Data input to be transmitted
3	RxD	Output	Received data output
4	CFG	Input	Configuration select, used to switch radio between data and control mode
5	RTS	Input	Request to send input, used for receive flow control by the host
6	Sleep/DTR	Input	Module sleep/DTR input, sleep is active high
7	DCD	Output	Data carrier detect, indicates successful synchronization on remotes
8	CTS	Output	Clear to send output, used for receive flow control by the radio
10	Reset	Input	Active low module reset input
16	Vcc	Power	Positive supply - minimum 3.3 V, nominal 5.0 V, maximum 10.0 V

### Physical Specifications - dimensions in inches (mm)

WIT2410M4G I/O pins point down for PCB interface as shown below.  
 WIT2410S4G I/O pins point up for cable connector interface.

