



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## **Features:**

- *Fast wireless serial data transmission*
- *Robust 2.4 GHz frequency hopping spread spectrum technology*
- *More than 1/2 mile outdoor range with omni-directional antennas*
- *3.3 volt operation, low power consumption*
- *Small size, light weight*
- *Certified for unlicensed operation in the USA, Canada and Europe*

## **Benefits:**

- *High immunity to interference and multipath fading*
- *Suitable for point-to-point and point-to-multipoint networks*
- *Worldwide license-free operation*
- *Easy to integrate*
- *Efficient in battery powered applications*
- *RoHS Compliant*

WIT2492 transceiver modules are designed to transmit serial data using highly robust, low latency 2.4 GHz frequency hopping spread spectrum (FHSS) technology. WIT2492 modules employ Murata's patented beacon-synchronized TDMA at an RF data rate of 921.6 kb/s, and can simultaneously support up to five continuously transmitting remotes. WIT2492 transceivers are suitable for both point-to-point and point-to-multipoint networks. FHSS technology provides strong immunity to both interference and multipath fading. The small size, light weight and low power consumption of the WIT2492 makes it suitable for a wide variety of applications. WIT2492 modules are certified for unlicensed operation in the USA, Canada and Europe.

## **Fast and Versatile**

WIT2492 modules transmit at an RF data rate of 921.6 kb/s using beacon-synchronized TDMA to achieve very low transmission latency in point-to-point cable replacement applications or point-to-multipoint (star) network applications. Serial communications between a WIT2410 module and its host can run at up to 460.8 kb/s to further speed data communication.

## **Efficient Battery Operation**

With +18 dBm of transmit power and a receive sensitivity of -90 dBm, the WIT2492 can achieve ranges in excess of 1/2 miles using 3 dBi omni-directional antennas. The WIT2492, measuring just 80.2 x 46.5 x 8.6 mm and weighing only 35 grams, is a powerful performer at low power. Consuming only 40 mA average current while streaming data continuously, WIT2492 remote units are ideal for lightweight battery powered applications.

## **Reliable**


The WIT2492 provides both reliable communications and reliable operation. The WIT2492's robust high-intercept RF front end provides excellent immunity to strong out-of-band signals such as pager transmitters and cellular phone systems. In addition, the frequency hopping spread spectrum technology used by the WIT2492 resists jamming by in-band signals and minimizes the effects of multipath fading. Using a 24-bit CRC for error detection and automatic retransmit request (ARQ), error-free communication is automatic. A network lockout key provides security from eavesdropping. Reliable operation is assured through RFM's stringent QA processes. All WIT2492s are manufactured in an ISO9000 certified facility.

## **Simple**

The WIT2492, with its small size and low power consumption, is simple to integrate into your product. The WIT2492's RS-232 style interface with standard 3.3 volt CMOS signal levels makes integration easy. Since WIT2492 modules are certified for license free operation, WIT2492 based product does not have to repeat radio regulatory approval.

# **WIT2492**

## **2.4 GHz FHSS Transceiver Module**



**Shown with shield removed**

RF Frequency	2400 to 2483.5 MHz					
Radio Certifications	FCC Part 15, Canadian RSS-210 and European ETS300 328					
Operating Range	Indoor: 300 to 700 ft, Outdoor - more than 1/2 mile with omni-directional antenna					
Network Topologies	Point-to-point and point-to-multipoint (star)					
Network Protocol	Low latency TDMA					
Error Detection and Correction	24-bit CRC and ARQ					
Serial Data Interface	Asynchronous (UART) CMOS signals, 3.3 V, 5 V tolerant					
Serial Data Rate	9.6 to 460.8 kb/s, software selectable					
Channel Data Rate	921.6 kb/s					
Number of Frequency Channels	43					
Transmit Power Output	+8 or +18 dBm, software selectable					
Receiver Sensitivity	-90 dBm for 10 <sup>-5</sup> BER					
RF Bandwidth	1.5 MHz					
Supply voltage	3.3 to 10 V					
Current Consumption 18 dBm Transmit Power, 115.2 kb/s Serial Data Rate	Remote Operation:	Sleep Standby Typical Peak (TX)	50 $\mu$ A 22 mA 40 mA 90 mA	Base Station Operation:	Continuous Peak (TX)	90 mA 100 mA
Size	80.2 x 46.5 x 8.6 mm					
Weight	35 g					
Operating Temperature	-40 C to 70 C					
Humidity	20% to 90% (non-condensing)					

Pin	Signal	Type	Description
1	Gnd	-	Signal and chassis ground
2	TxD	Input	Data input to be transmitted
3	RxD	Output	Received data output
4	CFG	Input	Configuration select, used to switch radio between data and control mode
5	RTS	Input	Request to send input, used for receive flow control by the host
6	Sleep/DTR	Input	Module sleep/DTR input, sleep is active high
7	DCD	Output	Data carrier detect, indicates FHSS synchronization on remotes
8	CTS	Output	Clear to send output, used for receive flow control by the radio
10	Power Down	Input	Low power mode input, active low
16	Vcc		Positive supply - minimum 3.3 V

### Physical Specifications - dimensions in inches (mm)

