



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



WP03-05-06-11 Series

8-10 WATT AC ADAPTERS

Features

- Two pin NEMA 5/15 input plug
- Output connector: barrel type:
(5.5 x 2.5 x 9.5mm)
- Wide range AC input
- Level B EMI filter
- Fully enclosed plastic case
- Fully regulated output



Elpac Model	Vdc	Amps	Watts (max)
WP0303-760	3.3	1	3.3
WP0312-760	12	0.25	3
WP0315-760	15	0.2	3
WP0503-760	3.3	1.5	5
WP0505-760	5	1	5
WP0605-760	5	1.2	6
WP0606-760	6	1	6
WP0609-760	9	0.67	6
WP0610-760	10	0.6	6
WP0612-760	12	0.5	6
WP0615-760	15	0.4	6
WP1105-760	5	1.5	7.5
WP1106-760	6	1.33	8
WP11075-760	7.5	1	7.5
WP1109-760	9	1	9
WP1110-760	10	1	10
WP1112-760	12	0.8	9.6
WP1115-760	15	0.63	9.5

Specifications

Input

- Voltage: 100-240 VAC (wide range)
- Current: 0.2 Amp
- Frequency: 47-63 Hz

Output

- Hold up time: 20ms minimum at full load, 115V
- Line regulation: TYP $\pm 1\%$ over 100-240 VAC
- Load regulation: TYP $\pm 5\%$
- Set point: $\pm 3\%$ at 60% load
- Over voltage protection: Built-in
- Over current protection: 150% of max load
- Short circuit protection: Pulsing mode, auto recovery

- Efficiency: 75% at full load & 115VAC
- Ripple/noise (V_{PP}): $\pm 1\%$ (20 MHz)

Environmental

- Operating temperature: 0°C to 40°C
- Storage temperature: -55°C to 85°C

EMI

- Meets FCC class B, CISPR 22 class B

Mechanical

- Size: 2.25 x 1.88 x 1.03 inches

Safety

- UL1950
- cUL-CSA 22.2 No. 950
- CE-Marked

Polarity



ELPAC POWER SYSTEMS

1562 Reynolds Ave • Irvine CA, 92614
Phone: (949) 476-6070 Fax: (949) 476-6075
Toll free: (888) ELPAC80
E-mail: sales@elpac.com or engr@elpac.com

www.elpac.com