



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Weller
60 Watts, 240v Temperature Controlled Soldering Station



◀◀ previous print close next ▶▶

Product Details

Catalog No.	WTCPTD
UPC Code	037103001122
Wattage	60 W
Soldering Pencil (s)	42 W
Temperature Range	600° F/ 700° F/ 800° F
Voltage Input/ Output	240 V/ 24 V
Supplied Tip(s)	PTA7
Iron Stand	PH1201ESD
Temperature Accuracy	Not Specified
Packaging	Industrial Box/ Carton
Tech. Spec.	Solder Safety Warnings.pdf
Lineart	WTCPT.pdf
Low Res. Image	WTCPTD_100.jpg
High Res. Image	WTCPTD_300.jpg
Stock Item	Normal Stock Item

Package Details (Dimensions)

[Email this Page](#)

Product Features:

- PU240T power unit, TC201T soldering pencil, PH1201ESD stand and sponge
- A lighted rocker switch indicates on/ off status
- Quick disconnect plug for soldering iron allows fast iron change
- Power unit features impact resistant plastic for durability
- Comes with PTA7 tip
- ESD safe to protect sensitive components
- Tips available in 3 standard temperature ranges: 600° F, 700° F, and 800° F
- UL and cUL listed