



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# WXR3

3-Channel Power Unit, 420 W (600 W)  
Product no.: WXR3N



## Benefits

- › Up to three 200w high performance tools can be operated simultaneously for up to 600 watts of total power on the 3-channel, WXR3 rework system
- › Used for soldering and desoldering of both large and small SMT components
- › 2 internal pumps provide the sources for hot air, desoldering vacuum and a vacuum pick up tool for a completely self-contained rework system
- › LCD display simultaneously monitors all parameters, connected tools and peripheral devices.
- › Adjust parameter setting and other functions through menu
- › Compatible with all WX tools, accessories, and peripherals



For this purpose, we recommend:



Solder fume extractors



Soldering irons



Cleaning




Pre-heating plates



### Technical Data

Dimensions L x W x H (mm)	273 x 235 x 102
Dimensions L x W x H (inches)	10,75 x 9,25 x 4,02
Weight (approx.) in kg	6.7
Voltage	120 V
Power	420 W (600 W)
Channels	3
Temperature range (depends on tool) °C	100 - 450 (550)
Temperature range (depends on tool) °F	200 - 850 (999)
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding socket	Via 3.5 mm pawl socket on back of device (Hard grounded)
Display	255 x 128 dots / Backlighting
Air consumption l/min	---
Operating pressure in bar/psi	---
Capacity l/min	18, max.
Vacuum	---

### Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE