

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











## DIGI XBEE® CELLULAR DEVELOPMENT KIT

XBee Cellular LTE Cat 1 development kit provides OEMs with a simple, quick way to integrate cellular connectivity into their devices.

The new Digi XBee Cellular embedded modem brings together the power and flexibility of the XBee ecosystem with the latest in 4G cellular technology. OEMs can quickly integrate cutting edge 4G cellular into their devices and applications, eliminating the painful, time-consuming and expensive FCC and carrier end-device certification process. Digi's XBee Cellular Development Kit offers a great way to learn how to integrate cellular connectivity using XBee embedded modems. Starting with simple examples, we provide step-bystep guidance as you assemble the kit components to create reliable, low-power cellular communications for OEM devices like sensors and control/monitoring systems. The kit will include 6 months of free cellular data service, pre-activated and ready to go right out of the box, allowing developers to immediately focus on their primary goal; developing great products without the hassle of setting up data plan, ordering and provisioning a SIM from the carrier.

This kit is designed for anyone interested in getting started in the world of embedded cellular. Hardware and software engineers, corporate technologists, or educators and students can quickly learn more about cellular integration using the hands-on examples included in the kit.

With the full suite of standard XBee API frames and AT commands, existing XBee customers can seamlessly transition to this new embedded modem with only minor software

## The Kit Includes:

- ✓ 1 XBee Cellular LTE Cat 1 embedded modem
- ✓ 1 XBee Development Board
- ✓ 1 LTE Cat 1 SIM for Verizon
- √ 6 months of free cellular service\*
- Antennas and power supply


NUMBER	DESCRIPTION
XKC-V1T-U	Digi XBee Cellular LTE Cat 1 Development Kit, Verizon LTE Cat 1, USA


\*Service will be limited to ~5MB/month and limited SMS. For testing purposes only, not for production.


adjustments. When OEMs add the XBee Cellular to their design, they create a future-proof design with flexibility to switch between wireless protocols or upgrade to LTE Cat M1 or NB1 as those networks are deployed—ideal for any OEM business with an agile roadmap.




SPECIFICATIONS	Digi XBee® Cellular LTE Cat 1
INTERFACES AND HARDWARE	
SERIAL DATA INTERFACE	UART (SPI coming soon)
ANALOG I/O	4 ADC lines (coming soon)
DIGITAL I/O	15 DIO lines (coming soon)
FORM FACTOR	20-pin XBee through-hole
ANTENNA OPTIONS	2 U.FL for primary and secondary antennas
DIMENSIONS	0.960 x 1.297 in (2.438 x 3.294 cm)
CHIPSET REFERENCE	Telit/Altair
OPERATING TEMPERATURE	-40° C to +80° C
RF CHARACTERISTICS	
MODULATION	LTE/4G - QPSK, 16QAM
TRANSMIT POWER	23dBm
RECEIVE SENSITIVITY	-102 dBm
NETWORKING AND CARRIER	
CARRIER AND TECHNOLOGY	Verizon 4G LTE Cat 1
SUPPORTED BANDS	4/13
SECURITY	SSL/TLS (Up to 1.2)
DATA RATES	921 Kbps via UART
POWER REQUIREMENTS	
SUPPLY VOLTAGE	3.0 to 5.5v
TRANSMIT CURRENT	860 mA average, 1020 mA Peak @ 3.3V
RECEIVE CURRENT	530 mA average @ 3.3V
IDLE CURRENT (LISTENING)	143 mA @ 3.3V
DEEP SLEEP	Approximately 10µA
REGULATORY AND CARRIER APPROVALS	
FCC (USA)	Contains: FCC: RI7LE866SV1
IC (CANADA)	Contains: IC: 5131A-LE866SV1
VERIZON END-DEVICE	Certified and ready for immediate use









It's the easy and fast way to build a wireless cellular device using Digi's XBee modules. To learn more visit www.digi.com/xbeecellular.

