imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







BUILD NETWORK CONNECTIVITY INTO YOUR PRODUCTS, QUICKLY AND SIMPLY

XPort[®] is a compact, integrated solution to web-enable any device with serial capability. By incorporating XPort to a product design, manufacturers can offer network connectivity as a standard feature within weeks — so they can be accessed and controlled over the Internet.

Full Networking in a Tiny Package

XPort removes the complexity – of designing network connectivity into a product by incorporating all of the required hardware and software inside a single embedded solution. Smaller than your thumb, it includes all essential networking features, including a 10Base-T/100Base-TX Ethernet connection, proven operating system, an embedded web server, e-mail alerts, a full TCP/IP protocol stack and 256-bit AES encryption for secure communications. This easy-to-embed networking processor module enables engineers to focus on their core competency while reducing development time and cost and increasing product value.

Integrated Network Communications Module

XPort is powered by our DSTni[™] network processor SoC, which includes a 10/100 MAC/PHY and 256 KB of SRAM. It features a built-in web server for communications with a device via a standard Internet browser. Web capability can be used for remote configuration, real-time monitoring or troubleshooting. XPort has 512 KB of on-module Flash for web pages and software upgrades. It acts as a dedicated co-processor that optimizes network activities permitting the host microprocessor to function at maximum efficiency.

Building Intelligent Devices

With XPort you can embed intelligence into any electronic product for applications such as:

- Remote diagnostics and upgrades
- Asset tracking and replenishment
- Automation and control
- Power management
- Remote collaboration
- Personalized content delivery

XPort Highlights

- Minimal engineering effort required to web-enable virtually any electronic device
- Remote command and control of edge devices
- 256-bit AES encryption for secure communications
- EM C/EMI -compliant; RoHS-compliant
- Everything you need all in a single RJ45 package







Robust, feature-rich software suite eliminating the need to negotiate the intricacies of Transmission Control Protocol (TCP) or Internet Protocol (IP), XPort incorporates:

- Robust Real Time Operating System (RTOS)
- Full-featured network protocol stack
- Built-in web server for device communication and configuration via a standard browser

The Windows[®]-based DeviceInstaller[™] makes configuring one or more XPorts in a subnet quick and easy

- Install and configure XPort and load firmware
- Assign IP & other network specific addresses
- · Load custom web pages and view specific device data
- Enable web-based configuration of the device
- $\boldsymbol{\cdot}$ Ping or query the attached device(s) over the network
- Allow Telnet communication with the device(s)

Features and Specifications

Serial Interface

• Interface: CMOS (Asynchronous, 5V tolerant)

- Data Rates: 300 bps to 921,600 bps
- Characters: 7 or 8 data bits
- Parity: odd, even, none
- Stop Bits: 1 or 2
- Control Signals: DTR/DCD, CTS, RTS
- Flow Control: XON/XOFF, RTS/CTS
- Programmable I/0: 3 PIO pins (software selectable)

Network Interface

- Interface: Ethernet 10Base-T or 100Base-TX (Auto-Sensing)
- Connector: RJ45
- Protocols: TCP/IP, UDP/IP, ARP, ICMP, SNMP, TFTP, Telnet, DHCP, BOOT P, HTTP and AutoIP

Indicators (LED)

- 10Base-T connection
- 100Base-TX connection
- Link & activity indicator Full/half duplex

Management

 \bullet SNMP, Telnet, serial, internal Web server and Microsoft $^{\otimes}$ Windows-based utility for configuration

Security

- Password protection
- Optional 256-bit AES Rijndael encryption

Internal Web Server

Storage capacity: 384 KB for web pages

Architecture

- CPU: Based on the DSTni-EX enhanced 16-bit, 48MHz or 88MHz x86
 architecture
- Memory: 256 KB SRAM and 512 KB Flash
- Firmware: upgradeable via TFTP and serially

Power

Input voltage: 3.3 VDC

Environmental

- Extended Temp: -40° to 85°C (-40° to 185°F)
- Storage: -40° to 85°C (-40° to 185°F)

Packaging

- Dimensions: 33.9 x 16.25 x 13.5 mm (1.33 x .64 x .53 in)
- Weight: 9.6 g (0.34 oz)

Warranty

2-year limited warranty

Included Software

- MS Windows-based DeviceInstaller software and MS Windows-based Com Port Redirector $^{\rm \tiny M}$

XPort Evaluation Kit

The XPort Evaluation Kit includes everything you need to integrate the XPort into your next product design, including:

- \cdot An XPort Evaluation Board and reference design including CAD PCB files and complete BOM
- Universal AC power adapter
- Network (CAT5) and serial cable
- Connector adapter

Part Number	Description
XP1001000-05R	XPort XE Min. Quantity: 50 Units XPort RoHS Extended Temperature, without Encryption
XP1001000M-05R	XPort XE RoHS Extended Temperature, with MODBUS, without Encryption XPort SE Min. Quantity: 50 Units
XP1002000-05R	XPort RoHS Extended Temperature, with Encryption
XP100200S-05R	XPort RoHS Extended Temperature, with Encryption- Sample
XP10010NMK-01	XPort Evaluation Kit, with Encryption
XPPDK1000-LNX-02	XPort Pro Linux Development Kit**

Ordering Information

Americas 800.422.7055 sales@lantronix.com http://www.lantronix.com

http://www.lantronix.com NASDAQ: LTRX

Europe +31 (0) 76.52.3.6.74 4 EMEA@lantronix.com

Asia/Pacific/Japan

+852 3428.2338 asiapacific_sales@lantronix.com

China: +86.21.6237.8868 Shanghai@lantronix.com

India: +91 994-551-2488 Sales_India@Iantronix.com

Japan: +81.3.3273.8850 Sales_Japan@lantronix.com



©2016 Lantronix, Inc. Lantronix and XPort are registered trademarks, and DSTni, DeviceInstaller and Com Port Redirector are trademarks of Lantronix, Inc. All other trademarks are the property of their respective owners. Specifications subject to change without notice. All rights reserved. MPB-00019 Rev B

LANTRONIX