



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# XT-MICRO-C-SXL



■ MADE  
■ IN  
■ GERMANY



**Parallel Printserver for integration of printers in an  
Ethernet network**

## Hardware description



Stecker

## Supported systems

1. Windows
2. Linux
3. UNIX

## Supported protocols IP-Dual-Stack

- |            |                          |
|------------|--------------------------|
| 1. IPv4    | 20. IPv6                 |
| 2. TCP     | 21. NDP                  |
| 3. UDP     | 22. ICMPv6               |
| 4. FTP     | 23. DHCPv6               |
| 5. TFTP    | 24. TCPv6                |
| 6. ICMP    | 25. UDPv6                |
| 7. ARP     | 26. Netbios-NS           |
| 8. SNMP    | 27. LLMNR                |
| 9. LPR     | 28. ZeroConfig<br>-APIPA |
| 10. DHCP   | -AutoIP                  |
| 11. BOOTP  | 29. IP-Multicast         |
| 12. DNS    | 30. AK-M2M               |
| 13. TELNET | 31. IEEE802.1x           |
| 14. HTML   | 32. SSL 3.0              |
| 15. http   | 33. TLS1.0               |
| 16. DYNDNS | 34. TLS1.1               |
| 17. SMTP   | 35. TLS1.2               |
| 18. POP3   |                          |
| 19. SYSLOG |                          |

## Technical data

- **Temperature range:**  
-40°C .. + 70°C
- **Standards**  
CE / WEEE / RoHS  
EN 55022 Class B  
EN 55024 Class A
- **Power supply:**  
Power supply unit  
5 Volt / 850 mA
- **Dimensions (BxHxT):**  
45 x 48x 14 (mm)
- **Ethernet (MDIX)**  
10 Half Duplex  
10 Full Duplex  
100 Half Duplex  
100 Full Duplex  
AutoSensing
- **Centronics IEEE1284**  
36 Pins plug

## Management

1. Telnet
2. Browser

## Emulations and functions

- DYNDNS-Client
- FTP-Server
- LPR-Server
- 512KB internal Flashdrive
- Flash-File-System
- TCP/UDP -Client
- TCP/UDP -Server
- SYSLOG-Client
- M2M