



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Description

The Z-200SM is a small in-line filter designed to expedite the service delivery and improve the performance of digital subscriber line (DSL) services. This model fits all telephone sets, facsimile machines, answering machines, etc. individually or in groups. Our in-line filter design electronically isolates the high-speed DSL and HPN data streams from the voice band plain old telephone service (POTS) equipment. This design effectively blocks the DSL, HPN and other radio frequencies up to 400 Megahertz (MHz).

Features

- Isolates telephone equipment impedances from the xDSL and HPN systems
- Attenuate xDSL & HPN signals to phone equipment to prevent conversion to voice band signals
- Attenuate HPN signals to unbalanced phone equipment to prevent radiation into electronic equipment
- Minimize voice band interference --- transmission, signaling and supervision
- Excellent longitudinal balance
- Compatible with all major xDSL standards including ADSL Full Rate (ITU-T G.992.1), ADSL G.Lite (ITU-T G.992.2), ADSL2 (ITU-T G.992.3 and .4), ADSL2+ (ITU-T G.992.5 in analog mode), ADSL2++, VDSL (ITU-T G.993.1), VDSL2; also V.90 and Metallic Loop Testing compatible
- FCC 47 CFR Part 68, IC CS-03, UL 60950, and CSA 22.2 No. 60950 compliant and listed
- CE Mark certified
- RoHS and WEEE compliant



Z-200SM In-Line Filter

Applications

The Z-200SM filters are used with other Z-BLOCKER® filters distributed throughout the subscribers' premises to isolate all voice band equipment devices such as corded/cordless telephones, answering machines, fax machines, 56Kb/s and lower rate modems, automatic dialers, recorder connectors and satellite television set-top boxes.

The Z-200SM-ST in-line DSL filter is one of many filters manufactured by Excelsus for subscriber installed digital services within homes, offices, and hotels. Excelsus is the number one

Series 200 Z-BLOCKER® Filter Specifications

Line side differential input blocking impedance			
At 20 kHz			>2k
At 30 kHz			>3k
From 5 MHz to 10 MHz			>4k
From 10 MHz to 400 MHz			>2k
1 kHz insertion loss between 600Ω resistive			
Single filter			<0.7
With 5 filters			<0.8
1 kHz/2.8 kHz slope between 600Ω resistive			
Single filter			<0.1
With 5 filters			<0.8
DC resistance in Ohms			
Tip to Tip, and Ring to Ring			<50
Tip to Ring			>10M
Longitudinal Balance per IEEE method			
From 200 - 1 kHz			>58 dB
From 1 kHz - 3 kHz			>53 dB
Common mode rejection at 40 kHz and 1.1 MHz			>45dB
Low pass roll off (slope) between 600 Ohm and ADSL Transmission Unit - Remote			>24dB
Inter-Modulation Distortion First and Second order products			>60dB
Envelope Delay 300 Hz - 2800 Hz			<100μs
600Ω Return Loss into phone side with 600Ω line termination with ATU-R			
Single filter	SRL Low		>25dB
	ERL		>25dB
	SRL High		>24dB
+2 bridged filter	SRL Low		>29dB
	ERL		>22dB
	SRL High		>15dB
+4 bridged filter	SRL Low		>28dB
	ERL		>16dB
	SRL High		>9dB
Complex* Return Loss with ATU-R			
Single filter	SRL Low		>28dB
Single filter	ERL		>17dB
Single filter	SRL High		>9dB
+2 bridged filters	SRL Low		>20dB
	ERL		>11dB
	SRL High		>6dB
+4 bridged filters	SRL Low		>16dB
	ERL		>8dB
	SRL High		>4dB
* 1330Ω in parallel with (100nfd in series with 348Ω)			
DC Loop Current - Meets specifications between 20 and 100 milliamps DC			
Isolates dial pulses and on-hook/off-hook transitions from the digital subscriber line			
Dimensions: Length 2.0in (50.8mm), Width 1.25in (31.75mm), Height .75in (19.05mm), Cord Length = 3.5in (88.9mm)			
US Pat. No. 6,212,259 and Taiwan Pat. No. 152847			