

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









REV RELEASED DESCRIPTION/ECO NO. 10/13/08 DATE

ELECTRICAL & OPTICAL CHARACTERISTICS

JKL	FORWARD	/ARD	FORWARD	/ARD	OPERATING	ATING	INTENSITY	SITY	PEAK	COLOR	Ž	TYP. VIEWING
PART	VOLTA	VOLTAGE (DC) CURRENT (mA)*	CURREN	T (mA)*	TEMP. (C)	(C)	mcd**	d **	WAVELENGTH	LED SOURCE	LENS TYPE	1/2 ANGLE
NUMBER	TYP.	MAX.	TYP.	MAX.	MN.	MAX.	MIN.	TYP.	nm	(DICE)	TYPE	DEGREE
7 24 20	17	ر د	3	25	20	+07	л О	ч с	033	RED	RED	16
7-212-8	1./	<u>.</u>	5	67	4	COT	0.0	۷.۵	000	GaAsP	TRANSPARENT	Ī
7 24 26 1	ა) n	5	26	20	- 05		3 C F	3 C3	HIGH EFFICIENCY	RED	10
7-21270		۷.5	5	23	-40	703	0.0	12.5	020	RED GaAsP/GaP	TRANSPARENT	10
2010	၁ ၁	n O	5	25	_	404		0.03	232	GREEN	GREEN	30
Z-Z Z G	2.2	۲.	5	2	5	100	0.0	0.0	505	GaP	TRANSPARENT	o o
7010	2) J	5	٦ ا	20	407	407	0.00	003	YELLOW	YELLOW	16
1717-7		۲.	5	2	4	100	12.3 20.0	٥.٥	390	GaAsP/GaP	TRANSPARENT	ō

- * CONTINUOUS-DUTY RATING

 ** INTENSITY VALUES ARE AT TYPICAL FORWARD CURRENT OF 10mA

NOTE: ELECTRO STATIC DISCHARGE PROTECTION REQUIRED WHEN HANDLING DEVICES.

- CAD D MANUAL REVISIO	DRAWN BY APPV'D BY DATE L. WENGSTROM L.R. 10/13/08	THIRD ANGLE PROJECTION	METRIC
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED	APPV'D BY DATE L.R. 10/13/08	TOLERANCE UNLESS OTHERWISE SPECIFIED ±0.25mm (±0.01)	DIMENSIONS ARE IN MILLIMETERS (INCHES)
SCALE	A	TITLE	T
NONE	55335 DRAWING	T-1 3 ROU	KL
NONE RELEASED 10/13/08 DATE	DRAWING NO.	T-1 3/4 (5mm) STAND-OFF LEAD ROUND LED LAMP	JKL COMPONENTS CORPORATION
REVISION DATE	Z-212	ND-OFF LEAI	NTS CORP
REV NO			ORAT
SHEET 1 OF 1			ION