Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!


Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Z86C4001ZDV
Z86C40 PLCC EMULATION POD-CCP

GENERAL DESCRIPTION

The Z86C40 PLCC Emulation Pod is specifically designed to enable Zilog's Z8® MCU CCP™ Emulator to emulate the 44-pin PLCC of devices listed below. The kit is a cost-ef- fective cable assembly allowing the use of an existing em- ulator.

SUPPORTED DEVICES

Packages	Devices
44-Pin PLCC	Z86C40
44-Pin PLCC	Z86C43
44-Pin PLCC	Z86243
44-Pin PLCC	Z86E43
44-Pin PLCC	Z86743
44-Pin PLCC	Z86E44

SPECIFICATIONS

Dimensions

Width: 1.400 in. (3.56 cm)
Length: 2.350 in. (5.97 cm)

Power Requirements

Not Applicable

Operating Temperature

20°C, ±10°C

Operating Humidity

10-90% RH (non-condensing)

PACKAGE CONTENTS

Hardware

Qty.	Description
1	Z86C40 PLCC Emulation Pod
1	40-pin PDIP/Emulation Cable

Documentation

Z86C4001ZDV PLCC Emulation Pod User's Guide

ADDITIONAL ITEMS REQUIRED (NOT SUPPLIED)

■ Zilog Z8 CCP Emulator (Z86CCP00ZEM)

■ Your Target Design: Typically, this is a wire-wrapped or printed-circuit prototype that includes a 44-pin PLCC socket for the target device, into which you can plug the emulation cable from the emulator.