



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




FC1-25-02-T-WT



ZF1-25-01-T-WT



FC1-20-01-T



ZF1-10-01-T-WT



ZF1, FC1 SERIES

(1.00 mm) .0394"

FLAT FLEXIBLE CABLE (FFC) SOCKET

Mates with:
FJ

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?ZF1

Insulator Material: Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating: Sn over 40 μ" (1.02 μm) Ni
Weld Tab: Phosphor Bronze
Operating Temp Range: -55 °C to +105 °C
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0.10 mm) .004" max

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



| ZF1 | NO. OF POSITIONS | LEAD STYLE | PLATING OPTION | WT | OPTION |
|-----|-----------------------------------|---|----------------|----------------|-----------------------------|
| | -05, -10, -15, -16, -20, -25, -30 | -01 = Contact Bottom -02 = Contact Top (10 positions only) | -T = Matte Tin | -WT = Weld Tab | -TR = Tape & Reel Packaging |

APPLICATION

ALSO AVAILABLE (MOQ Required)

- Other positions Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.

Mates with:
FJ

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?FC1

Insulator Material: Liquid Crystal Polymer
Contact Material: Phosphor Bronze
Plating: Sn over 50 μ" (1.27 μm) Ni
Operating Temp Range: -55 °C to +105 °C
Max Cycles: 25 with FJ
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0.10 mm) .004" max

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



| FC1 | NO. OF POSITIONS | LEAD STYLE | PLATING OPTION | OPTIONS |
|-----|--------------------------|------------------------------------|----------------|--|
| | -05, -10, -15, -20 & -25 | -01 = Vertical -02 = Horizontal | -T = Tin | -LC = Locking Clip (Manual placement required) (-01 only) -WT = Weld Tab (-02 only) -K = (4.00 mm) .158" DIA Polyimide film Pick & Place Pad (-01 only) -TR = Tape & Reel Packaging |

ALSO AVAILABLE (MOQ Required)

- Low insertion force contacts available Contact Samtec.