

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

DOUBLE WHITE LED FLEX RIBBON

Features

VOLTAGE: 12V DC
 CURRENT: 4200mA
 LED VIEWING ANGLE (2 θ 1/2): 120°

STANDARD PACKAGING:
 5 Meter Reel (300 LED's)

OPTIONAL PACKAGING:
 Individual 500mm Sections (30 LED's)
 Order as ZFS-105000-DBW/XXSEC
 Note: Individual Sections ARE NOT supplied
 with insulated wire connection.



Maximum Ratings


Parameter	Symbol	Rating	Unit
Electrostatic Discharge	ESD	800	V
Operating Temperature	Topr	-0~+40	°C
Storage Temperature	Tstg	-40~+100	°C

Accessories

ZCTR-05: RF Wireless Touch LED Remote Controller

Electro-Optical Characteristics (Ta = 25° C)

Color	Number of LED's per Reel	Input Voltage (V DC)	Power (W)	Current (A)	Radiance Angle	CCT (K)	Lumen Flux (lm)
Cool White	300	12	25.0	2.1	120°	6475	1740
Warm White	300	12	25.0	2.1	120°	3284	1620



ATTENTION
 OBSERVE PRECAUTION FOR HANDLING ELECTROSTATIC DISCHARGE SENSITIVE DEVICES

Note: Please refer to JKL Application Sheet JKL- AS-ZFS-105000-DBW LED FLEX for Installation and Power Recommendations.

		METRIC		DIMENSIONS ARE IN mm (INCHES)		 JKL COMPONENTS CORPORATION							
		 THIRD ANGLE PROJECTION		TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/-						TITLE DOUBLE WHITE 12V LED FLEX RIBBON			
B ADD UL SYMBOL		3/31/15		DRAWN BY L. WENGSTROM		APP'VD BY DATE S.C. 3/31/15		SIZE A		FSCM NO. 55335		DRAWING NO. ZFS-105000-DBW	
A ADD TAPE SYMBOL NOTE		10/9/14		RELEASED		3/18/14		SCALE NONE		RELEASED DATE 3/18/14		REVISION DATE 3/31/15	
REV. NO.		DESCRIPTION/ECO NUMBER		APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				REV. NO. B		SHEET 1 OF 1	