



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832



Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Sockets for RPY Relays


ZPY8A




General data

| | |
|-----------------------|--|
| Rated voltage | 300VAC |
| Rated current | 16A |
| Insulation voltage | >2kV |
| Socket material | PA66 + GF (V0) |
| Socket colour | RAL 7035 / Pantone 1C |
| Contact material | Nickel Plated - Cu Zn 33 |
| Terminal type | Screw cage |
| Screw type | M3 with combi head (slotted, Philips Gr.1, Pozi) |
| Max. screw torque | 1.0N/m |
| Max wire section | 0.5-2.5mm ² (20AWG 14AWG) |
| Operating temperature | -25° to +85°C (-13° to +185°F) |
| UL rating | 10A 300VAC |
| UL temperature | 0° to +60°C (+32° to +140°F) |

Drilling pattern



Wiring diagram



Approvals




Box content: 10 sockets
 Box size: (W 71 x D 57 x H 150) mm Weight: 480g
 (W 2.80 x D 2.25 x H 5.90) inches Weight: 16.93oz

Optional Accessories (to be ordered separately if required)

Hold-down spring steel SZPY 35M (see on page 101)

Optional Springs for ZPY series

SZPY 35M



General data

Spring material

Stainless steel

Packaging

Box content: 1 plastic bag, 10pcs.

Weight: ~10g (0.36oz)

Note:

For each reley/socket are required at least 2 springs.

Up to 4 springs can be mounted.

RoHS
COMPLIANT