



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ZXMC6A09DN8

COMPLEMENTARY 60V ENHANCEMENT MODE MOSFET


SUMMARY

N-Channel $V_{(BR)DSS} = 60V$; $R_{DS(ON)} = 0.045\Omega$; $I_D = 5.1A$

P-Channel $V_{(BR)DSS} = -60V$; $R_{DS(ON)} = 0.055\Omega$; $I_D = -4.8A$

DESCRIPTION

This new generation of trench MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.




SO8

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- Low profile SOIC package

APPLICATIONS

- Motor drive
- LCD backlighting




ORDERING INFORMATION

DEVICE	REEL	TAPE WIDTH	QUANTITY PER REEL
ZXMC6A09DN8TA	7"	12mm	500 units
ZXMC6A09DN8TC	13"	12mm	2500 units

DEVICE MARKING

ZXMC
6A09

PINOUT



Top view

ZXMC6A09DN8

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	N-Channel I	P-Channel	UNIT
Drain-Source Voltage	V_{DS}	60	-60	V
Gate-Source Voltage	V_{GS}	± 20	± 20	V
Continuous Drain Current @ $V_{GS}=10V$; $T_A=25^\circ C$ ^{(b)(d)} @ $V_{GS}=10V$; $T_A=25^\circ C$ ^{(b)(d)} @ $V_{GS}=10V$; $T_A=25^\circ C$ ^{(a)(d)}	I_D	5.1 4.1 3.9	-4.8 -3.8 -3.7	A A A
Pulsed Drain Current ^(c)	I_{DM}	25	-23	A
Continuous Source Current (Body Diode) ^(b)	I_S	3.5	-3.3	A
Pulsed Source Current (Body Diode) ^(c)	I_{SM}	25.4	-23.8	A
Power Dissipation at $T_A=25^\circ C$ ^{(a)(d)} Linear Derating Factor	P_D	1.25 10		W mW/°C
Power Dissipation at $T_A=25^\circ C$ ^{(a)(e)} Linear Derating Factor	P_D	1.8 14		W mW/°C
Power Dissipation at $T_A=25^\circ C$ ^{(b)(d)} Linear Derating Factor	P_D	2.1 17		W mW/°C
Operating and Storage Temperature Range	$T_J:T_{stg}$	-55 to +150		°C

THERMAL RESISTANCE






PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient ^{(a)(d)}	$R_{\theta JA}$	100	°C/W
Junction to Ambient ^{(b)(e)}	$R_{\theta JA}$	69	°C/W
Junction to Ambient ^{(b)(d)}	$R_{\theta JA}$	58	°C/W

Notes:

- (a) For a dual device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper in still air conditions.
(b) For a dual device surface mounted on FR4 PCB measured at $t \leq 10$ sec.
(c) Repetitive rating 25mm x 25mm FR4 PCB, $D=0.02$, pulse width=300 μ s - pulse width limited by maximum junction temperature.
(d) For a dual device with one active die.
(e) For a device with two active die running at equal power.

ZXMC6A09DN8

CHARACTERISTICS



ZXMC6A09DN8

N-CHANNEL

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	60			V	I _D =250μA, V _{GS} =0V
Zero Gate Voltage Drain Current	I _{DSS}			1.0	μA	V _{DS} =60V, V _{GS} =0V
Gate-Body Leakage	I _{GSS}			100	nA	V _{GS} =±20V, V _{DS} =0V
Gate-Source Threshold Voltage	V _{GS(th)}	1.0			V	I _D =250μA, V _{DS} = V _{GS}
Static Drain-Source On-State Resistance ⁽¹⁾	R _{DS(on)}			0.045 0.070	Ω Ω	V _{GS} =10V, I _D =8.2A V _{GS} =4.5V, I _D =7.4A
Forward Transconductance ⁽¹⁾⁽³⁾	g _{fs}		15		S	V _{DS} =15V, I _D =8.2A
DYNAMIC ⁽³⁾						
Input Capacitance	C _{iss}		1407		pF	V _{DS} =40V, V _{GS} =0V, f=1MHz
Output Capacitance	C _{oss}		121		pF	
Reverse Transfer Capacitance	C _{rss}		59		pF	
SWITCHING ^{(2) (3)}						
Turn-On Delay Time	t _{d(on)}		4.9		ns	V _{DD} =30V, I _D =1.0A R _G 6.0Ω, V _{GS} =10V
Rise Time	t _r		3.3		ns	
Turn-Off Delay Time	t _{d(off)}		28.5		ns	
Fall Time	t _f		11.0		ns	
Gate Charge	Q _g		12.4		nC	V _{DS} =15V, V _{GS} =5V, I _D =3.5A
Total Gate Charge	Q _g		24.2		nC	V _{DS} =15V, V _{GS} =10V, I _D =3.5A
Gate-Source Charge	Q _{gs}		5.2		nC	
Gate-Drain Charge	Q _{gd}		3.5		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage ⁽¹⁾	V _{SD}		0.85	0.95	V	T _J =25°C, I _S =6.6A, V _{GS} =0V
Reverse Recovery Time ⁽³⁾	t _{rr}		26.3		ns	T _J =25°C, I _F =3.5A, di/dt= 100A/μs
Reverse Recovery Charge ⁽³⁾	Q _{rr}		26.6		nC	

NOTES

(1) Measured under pulsed conditions. Width $\leq 300\mu\text{s}$. Duty cycle $\leq 2\%$.

(2) Switching characteristics are independent of operating junction temperature.

(3) For design aid only, not subject to production testing.

ZXMC6A09DN8

P-CHANNEL

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	-60			V	I _D =-250μA, V _{GS} =0V
Zero Gate Voltage Drain Current	I _{DSS}			-1.0	μA	V _{DS} =-60V, V _{GS} =0V
Gate-Body Leakage	I _{GSS}			100	nA	V _{GS} =±20V, V _{DS} =0V
Gate-Source Threshold Voltage	V _{GS(th)}	-1.0			V	I _D =-250μA, V _{DS} = V _{GS}
Static Drain-Source On-State Resistance ⁽¹⁾	R _{DS(on)}			0.055 0.080	Ω Ω	V _{GS} =-10V, I _D =-3.5A V _{GS} =-4.5V, I _D =-2.9A
Forward Transconductance ⁽¹⁾⁽³⁾	g _{fs}		8.7		S	V _{DS} =-15V,I _D =-3.5A
DYNAMIC ⁽³⁾						
Input Capacitance	C _{iss}		1580		pF	V _{DS} =-30 V, V _{GS} =0V, f=1MHz
Output Capacitance	C _{oss}		160		pF	
Reverse Transfer Capacitance	C _{rss}		140		pF	
SWITCHING ^{(2) (3)}						
Turn-On Delay Time	t _{d(on)}		4.6		ns	V _{DD} =-30V, I _D =-1A R _G 6.0Ω, V _{GS} =-10V
Rise Time	t _r		5.8		ns	
Turn-Off Delay Time	t _{d(off)}		55		ns	
Fall Time	t _f		23		ns	
Gate Charge	Q _g		23		nC	V _{DS} =-30V,V _{GS} =-5V, I _D =-3.5A
Total Gate Charge	Q _g		44		nC	V _{DS} =-30V,V _{GS} =-10V, I _D =-3.5A
Gate-Source Charge	Q _{gs}		3.9		nC	
Gate-Drain Charge	Q _{gd}		9.8		nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage ⁽¹⁾	V _{SD}		-0.85	-0.95	V	T _J =25°C, I _S =-4.2A, V _{GS} =0V
Reverse Recovery Time ⁽³⁾	t _{rr}		37		ns	T _J =25°C, I _F =-2.1A, di/dt= 100A/μs
Reverse Recovery Charge ⁽³⁾	Q _{rr}		56		nC	

NOTES


(1) Measured under pulsed conditions. Width $\leq 300\mu\text{s}$. Duty cycle $\leq 2\%$.

(2) Switching characteristics are independent of operating junction temperature.

(3) For design aid only, not subject to production testing.


ZXMC6A09DN8

N-CHANNEL TYPICAL CHARACTERISTICS




ZXM C6A09DN8

N-CHANNEL TYPICAL CHARACTERISTICS




ZXMC6A09DN8

P-CHANNEL TYPICAL CHARACTERISTICS




ZXMC6A09DN8

P-CHANNEL TYPICAL CHARACTERISTICS



ZXMC6A09DN8

PACKAGE OUTLINE



CONTROLLING DIMENSIONS ARE IN INCHES
APPROX IN MILLIMETERS

PACKAGE DIMENSIONS

DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min	Max	Min	Max		Min	Max	Min	Max
A	1.35	1.75	0.053	0.069	e	1.27 BSC		0.050 BSC	
A1	0.10	0.25	0.004	0.010	b	0.33	0.51	0.013	0.020
D	4.80	5.00	0.189	0.197	c	0.19	0.25	0.008	0.010
H	5.80	6.20	0.228	0.244	Θ	0°	8°	0°	8°
E	3.80	4.00	0.150	0.157	h	0.25	0.50	0.010	0.020
L	0.40	1.27	0.016	0.050	-	-	-	-	-

© Zetex Semiconductors plc 2005

Europe	Americas	Asia Pacific	Corporate Headquarters
Zetex GmbH Streitfeldstraße 19 D-81673 München Germany	Zetex Inc 700 Veterans Memorial Hwy Hauppauge, NY 11788 USA	Zetex (Asia) Ltd 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong	Zetex Semiconductors plc Zetex Technology Park Chadderton, Oldham, OL9 9LL United Kingdom
Telefon: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europa.sales@zetex.com	Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com	Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com	Telephone (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com



ISSUE 4 - MAY 2005